

Silver Stone Industries

A- 206, M.I.A., Madri, Udaipur - 313001 (Raj.) Telephone: +91 294 2490291 Email: silverstoneindustries@gmail.com sales@silverstoneindustries.com

Quality/Grade	Dolo Talc
Product Code	SDT

Typical Properties:

Dolo -Talc powder is a blend of Talc and Dolomite mineral. It is a mixture of physical, chemical and mechanical characteristics of Talc and Dolomite mineral.

Packed in 50 Kg HDPE Bags, should be stored in dry area and away from any source of moisture.

Physical Properties

Brightness 85 ~ 98% 87 ~ 99% Whiteness

Specific Gravity 2.75

0.10 % Max Moisture

Bulk Density $0.40 \sim 0.70$ (Depending on the Particle Size) Oil Absorption 19 ~ 23 (Depending on the Particle Size)


LOI $5 \sim 50 \%$

Chemical Properties

CaO	2.5 ~ 25 %
MgO	20 ~ 29 %
Al_2O_3	0.50 Max
Fe ₂ O ₃	0.50 Max
SiO ₂	10 ~ 55 %

Particle Size Range

D97	30 ∼10 µ
D50	7 ~ 3 μ



The information contained in this Technical Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. The information provided herein is based on technical data that Silver Stone Industries believes to be reliable, however Silver Stone Industries makes no representation or warranty as to the completeness or accuracy thereof and Silver Stone Industries assumes no liability resulting from its use or for any claims, losses, or damages of any third party.

Recipients receiving this information must exercise their own judgment as to the appropriateness of its use, and it is the users responsibility to assess the materials suitability (including safety) for a particular purpose prior to such use.